

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.62	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, determined longitudinally by proportionate measurement and latitudinally by fence extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>S 16</p> <p>1/4 ———</p> <p>S 21</p> <p>1997</p> </div> <hr/> <p>S. 89° 55' W., beginning new measurement.</p> <p>Over gently rolling terrain, along fence.</p>
17.80	Intersection of fences extending E., S. and W.
19.81	<p>Point for the W. 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>S 16</p> <p>W1/16 ———</p> <p>S 21</p> <p>1997</p> </div> <p>Cor. is located in fence extending E. and W.</p>
36.50	Intersection of fences extending E., W. and NNW.
39.62	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0° 41' W., bet. secs. 16 and 17.</p> <p>Over gently rolling terrain, converging with fence.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.59	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, determined latitudinally by proportionate measurement and longitudinally by fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W 1/4 S 17 S 16 1997</p> </div> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 38' W., beginning new measurement.</p> <p>Over gently rolling terrain, along fence.</p>
39.60	<p>The cor. of secs. 8, 9, 16 and 17, at old cor. post of intersection of fences extending N., S. and abandoned E. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W S 8 S 9 <hr style="width: 50%; margin: 0 auto;"/>S 17 S 16 1997</p> </div> <hr style="width: 60%; margin: 10px auto;"/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 88° 53' W., bet. secs. 9 and 16.</p> <p>Over gently rolling terrain, along increasing evidence of abandoned fence.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.165	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, determined longitudinally by proportionate measurement and latitudinally by abandoned fence extending E. and W.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>S 9</p> <p>1/4 —</p> <p>S 16</p> <p>1997</p> </div> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p>S. 88° 58' W., beginning new measurement.</p> <p>Over gently rolling terrain, along abandoned fence.</p>
40.165	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0° 50' W., bet. secs. 8 and 9.</p> <p>Over gently rolling terrain, along fence.</p>
8.20	<p>Wyoming State Highway No. 116, bears NE. and SW.</p>
20.155	<p>Point for the S. 1/16 sec. cor. of secs. 8 and 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>S 1/16</p> <p>S 8 S 9</p> <p>1997</p> </div>
40.31	<p>Cor. is located S. 3¼° E., 54.8 lks. dist., from intersection of fences extending N., S. and W.</p> <p>The 1/4 sec. cor. of secs. 8 and 9, at cor. of fences extending E. and S. This position is accepted as the best available evidence of the original cor. position.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>1/4</p> <p>S 8 S 9</p> <p>1997</p> </div> <hr/> <p>N. 3° 27' E., beginning new measurement.</p> <p>Over nearly level terrain.</p> <p>41.055 Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>S 5 S 4</p> <hr/> <p>S 8 S 9</p> <p>1997</p> </div> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89° 54' W., bet. secs. 4 and 9.</p> <p>Over gently rolling terrain.</p> <p>39.535 Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
--------	--

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p style="text-align: center;">T47N R65W S 4 1/4 — S 9 1997</p>
	Set a steel fence post alongside the iron post.
79.07	The cor. of secs. 4, 5, 8 and 9.
	<hr/>
	N. 1° 45' E., bet. secs. 4 and 5.
	Over gently rolling terrain.
0.60	Trail road, bears E. and W.
40.50	Trail road, on ridge, bears SE. and NW.; thence over rolling terrain.
41.00	Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	<p style="text-align: center;">T47N R65W 1/4 S 5 S 4 1997</p>
	Set a steel fence post alongside the iron post.
82.28	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.
	<hr/>
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.
	N. 4° 33' E., bet. secs. 31 and 32.
	Over gently rolling terrain, leaving fence.
41.52	The 1/4 sec. cor. of secs. 31 and 32, monumented with a sandstone, 18X10X2 ins., firmly set 11 ins. in the ground, no mks. visible, in projection of fence from the N. This position is accepted as the best available evidence of the original cor. position.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	<div style="text-align: center;"> T47N R65W 1/4 S 31 S 32 1997 </div>
	Bury the unmkd. stone and set a steel fence post alongside the iron post.
	<hr/>
	N. 3° 37' W., beginning new measurement.
	Over rolling terrain.
20.15	Cor. of fences extending N. and W.; thence along fence.
38.75	Intersection of fences extending N., S. and W.
40.43	The cor. of secs. 29, 30, 31 and 32, monumented with a sandstone, 21X7X4 ins., firmly set 14 ins. in the ground, no mks. visible, at cor. of fences extending E. and S. This position is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.
	<div style="text-align: center;"> T47N R65W S 30 S 29 <hr/> S 31 S 32 1997 </div>
	<hr/>
	From the cor. of secs. 28, 29, 32 and 33.
	S. 88° 30' W., bet. secs. 29 and 32.
	Over rolling terrain.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.72	<p>The 1/4 sec. cor. of secs. 29 and 32, at cor. of fences extending S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>S 29</p> <p>1/4 —</p> <p>S 32</p> <p>1997</p> </div> <hr/> <p>N. 89° 41' W., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p>
0.36	<p>Recently constructed intersection of fences extending N., E. and W.</p>
43.63	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>S. 89° 12' W., bet. secs. 30 and 31.</p> <p>Over gently rolling terrain.</p>
39.87	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>S 30</p> <p>1/4 —</p> <p>S 31</p> <p>1997</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 44 lks. N. of fence extending E. and W.</p>
79.35	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	From the cor. of secs. 29, 30, 31 and 32.
	N. 4° 56' E., bet. secs. 29 and 30.
	Over rolling terrain.
29.30	Ridge, bears E. and W.
40.01	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a sandstone, 10X7X3 ins., loosely set 6 ins. in the ground, no mks. visible, in a small, embedded collar of stone. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>1/4</p> <p>S 30 S 29</p> <p>1997</p> </div> <p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	N. 0° 57' W., beginning new measurement.
	Over rolling terrain.
21.50	Ridge, bears E. and W.
40.30	<p>The cor. of secs. 19, 20, 29 and 30, monumented with a sandstone, 21X18X3 ins., firmly set 9 ins. in the ground, no mks. visible, with a sandstone, 14X9X5, lying alongside, no mks. visible, at cor. post of abandoned fences extending N. and E. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<div data-bbox="873 310 1024 464" data-label="Text"> <p>T47N R65W S 19 S 20 ----- S 30 S 29 1997</p> </div> <div data-bbox="440 499 1450 558" data-label="Text"> <p>Bury the unmkd. stones and set a steel fence post alongside the iron post.</p> </div> <hr/> <div data-bbox="440 625 1089 655" data-label="Text"> <p>From the cor. of secs. 20, 21, 28 and 29.</p> </div> <div data-bbox="440 686 1008 716" data-label="Text"> <p>S. 89° 33' W., bet. secs. 20 and 29.</p> </div> <div data-bbox="440 749 769 779" data-label="Text"> <p>Over rolling terrain.</p> </div> <div data-bbox="293 812 786 842" data-label="Text"> <p>20.65 Fence, bears N. and S.</p> </div> <div data-bbox="293 875 1425 1098" data-label="Text"> <p>39.66 The 1/4 sec. cor. of secs. 20 and 29, monumented with a sandstone, 13X12X2 ins., firmly set 8 ins. in the ground, no mks. visible, with a sandstone, 11X7X1 ins., buried alongside, no mks. visible, with another sandstone, 15X12X5 ins., no mks. visible, and an iron pipe, 48 ins. long, 2 ins. diam., lying alongside. This position is accepted as the best available evidence of the original cor. position.</p> </div> <div data-bbox="433 1131 742 1161" data-label="Text"> <p>At the corner point</p> </div> <div data-bbox="433 1194 1414 1283" data-label="Text"> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> </div> <div data-bbox="868 1325 1016 1478" data-label="Text"> <p>T47N R65W S 20 1/4 ——— S 29 1997</p> </div> <div data-bbox="433 1514 1442 1575" data-label="Text"> <p>Bury the unmkd. stones and set a steel fence post alongside the iron post.</p> </div> <hr/> <div data-bbox="433 1642 1083 1671" data-label="Text"> <p>S. 89° 05' W., beginning new measurement.</p> </div> <div data-bbox="433 1705 1393 1761" data-label="Text"> <p>Over rolling terrain, along increasing evidence of abandoned fence.</p> </div> <div data-bbox="285 1795 1002 1829" data-label="Text"> <p>41.64 The cor. of secs. 19, 20, 29 and 30.</p> </div>
--------	--

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>S. 89° 35' W., bet. secs. 19 and 30.</p> <p>Over rolling terrain.</p>
39.97	<p>The 1/4 sec. cor. of secs. 19 and 30, at intersection of fences extending N., W. and abandoned S. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>S 19</p> <p>1/4 ———</p> <p>S 30</p> <p>1997</p> <hr/> </div>
40.52	<p>S. 89° 43' W., beginning new measurement.</p> <p>Over rolling terrain, along fence.</p> <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 1° 25' E., bet. secs. 19 and 20.</p> <p>Over gently rolling terrain, along fading abandoned fence.</p>
37.67	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T47N R65W</p> <p>1/4</p> <p> </p> <p>S 19 S 20</p> <p>1997</p> </div> <p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS

40.17

True point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance, falls in large stock reservoir where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.

46.60

Cor. of fences extending N. and E., on N. side of large stock reservoir; thence along fence.

80.34

The cor. of secs. 17, 18, 19 and 20, at intersection of fences extending N., E., S. and W. This position is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.

T47N R65W
S 18 S 17
S 19 S 20
1997

From the cor. of secs. 16, 17, 20 and 21.

S. 89° 01' W., bet. secs. 17 and 20.

Over rolling terrain, along fence.

39.68

The 1/4 sec. cor. of secs. 17 and 20, at intersection of fences extending N., E. and W. This position is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.

T47N R65W
S 17
1/4 —
S 20
1997

S. 89° 18' W., beginning new measurement.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	Over gently rolling terrain, along fence.
20.16	Point for the W. 1/16 sec. cor. of secs. 17 and 20. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd. <div style="text-align: center;"> T47N R65W S 17 W1/16 ——— S 20 1997 </div>
	Set a steel fence post alongside the iron post.
	Cor. is located 25 N. of fence extending E. and W.
40.32	The cor. of secs. 17, 18, 19 and 20. <hr/>
	N. 0° 01' W., bet. secs. 17 and 18.
	Over gently rolling terrain, along fence.
20.21	Point for the S. 1/16 sec. cor. of secs. 17 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd. <div style="text-align: center;"> T47N R65W S1/16 S 18 S 17 1997 </div>
	Cor. is located in fence extending N. and S.
30.50	Intersection of fences extending S., NW. and abandoned N.
40.42	The 1/4 sec. cor. of secs. 17 and 18, at projected intersection of abandoned fences from the N., S. and W. This position is accepted as the best available evidence of the original cor. position. At the corner point

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W 1/4 S 18 S 17 1997</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on N. edge of Brainard Draw, drains SE., on W. side of a large deadman tie down.</p> <hr/> <p>N. 1° 06' W., beginning new measurement.</p> <p>Over rolling terrain, along fading abandoned fence.</p> <p>39.86 Point for the cor. of secs. 7, 8, 17 and 18, determined latitudinally by proportionate measurement and longitudinally on projection of abandoned fence from the N.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W S 7 S 8 <hr/>S 18 S 17 1997</p> </div> <p>Set a steel fence post, with survey marker sign attached, alongside the iron post.</p> <p>Cor. is located in southern right-of-way ditch, Wyoming State Highway No. 116, extending E. and W.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89° 57' W., bet. secs. 8 and 17.</p> <p>Over gently rolling terrain.</p> <p>20.00 Enter right-of-way, Wyoming State Highway No. 116, bears NE. and W.</p>
--------	---

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
39.96	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, determined latitudinally by proportionate measurement and longitudinally by projection of fences from the N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>S 8</p> <p>1/4 ———</p> <p>S 17</p> <p>1997</p> </div> <p>Set a steel fence post, with survey marker sign attached, alongside the iron post.</p> <p>Cor. is located 45 lks. S. of center line, Wyoming State Highway No. 116, extending E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 57' W., beginning new measurement.</p> <p>Over gently rolling terrain, along Wyoming State Highway No. 116 right-of-way.</p>
39.22	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>N. 1° 44' E., bet. secs. 7 and 8.</p> <p>Over gently rolling terrain.</p>
0.58	<p>Wyoming State Highway No. 116, bears E. and W.; thence along increasing evidence of abandoned fence.</p>
21.00	<p>Trail road, on ridge, bears SE. and NW.</p>
39.87	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, determined latitudinally by proportionate measurement and longitudinally by abandoned fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<div data-bbox="873 310 1023 432" data-label="Text"> <p>T47N R65W 1/4 S 7 S 8 1997</p> </div> <div data-bbox="440 468 1187 499" data-label="Text"> <p>Set a steel fence post alongside the iron post.</p> <hr/> </div> <div data-bbox="440 562 1073 594" data-label="Text"> <p>N. 1° 17' E., beginning new measurement.</p> </div> <div data-bbox="440 625 1252 657" data-label="Text"> <p>Over gently rolling terrain, along abandoned fence.</p> </div> <div data-bbox="297 688 784 720" data-label="Text"> <p>18.80 Fence, bears E. and W.</p> </div> <div data-bbox="297 751 1219 783" data-label="Text"> <p>19.93 Point for the N. 1/16 sec. cor. of secs. 7 and 8.</p> </div> <div data-bbox="440 814 1414 909" data-label="Text"> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> </div> <div data-bbox="873 947 1023 1068" data-label="Text"> <p>T47N R65W N1/16 S 7 S 8 1997</p> </div> <div data-bbox="440 1104 1182 1136" data-label="Text"> <p>Set a steel fence post alongside the iron post.</p> </div> <div data-bbox="440 1167 1349 1262" data-label="Text"> <p>Cor. is located in abandoned fence extending N. and S., N. 63¾° E., 2.59 chs. dist., from existing cor. of fences extending N. and E.</p> </div> <div data-bbox="297 1293 1458 1388" data-label="Text"> <p>39.86 The cor. of secs. 5, 6, 7 and 8, at projected cor. of abandoned fences from the S. and W. This position is accepted as the best available evidence of the original cor. position.</p> </div> <div data-bbox="440 1419 740 1451" data-label="Text"> <p>At the corner point</p> </div> <div data-bbox="440 1482 1409 1577" data-label="Text"> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> </div> <div data-bbox="873 1614 1023 1766" data-label="Text"> <p>T47N R65W S 6 S 5 S 7 S 8 1997</p> </div> <div data-bbox="440 1797 1179 1829" data-label="Text"> <p>Set a steel fence post alongside the iron post.</p> </div>
--------	--

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Cor. is located N. 60$\frac{1}{4}$° E., 3.25 chs. dist., from recently constructed intersection of fences extending N., S. and W.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 88° 49' W., bet. secs. 5 and 8.</p> <p>Over gently rolling terrain.</p> <p>39.49 Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>S 5</p> <p>1/4 —</p> <p>S 8</p> <p>1997</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>78.98 The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>N. 0° 41' E., bet. secs. 5 and 6.</p> <p>Over rolling terrain.</p> <p>41.28 Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W</p> <p>1/4</p> <p>S 6 S 5</p> <p>1997</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on top of ridge extending SE. and NW., 3.45 chs. E. of fence extending N. and S.</p>
--------	---

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
61.60	Fence, bears E. and W.
61.92	<p>Point for the N. 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W N1/16 S 6 S 5 1997</p> <p>Cor. is located N. 85½° E., 3.92 chs. dist., from cor. of fences extending E. and S.</p>
82.40	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area embraced by this survey is situated in north central Weston County, with the town of Upton, Wyoming partially located in secs. 1 and 2. The terrain varies from nearly level to rolling, with elevations ranging from approximately 4,150 feet to 4,500 feet above sea level. The soil varies from sandy loam to bedrock, with the majority consisting of clays. Timber consists of ponderosa pine and juniper located primarily in section 1.</p> <p>Drainage is provided by numerous creeks, drainages and draw, all draining toward the southeast. There is one working ranch within the area surveyed, with numerous other working ranches holding lands within the area. There is evidence of limited oil and gas exploration in the past, although no producing wells are present. There is evidence of extensive bentonite mining activity, primarily in the northeast quarter, most of which has been reclaimed.</p> <p>Access is provided by Wyoming State Highway No. 116, by Upton-Fairview Road, and by numerous private roads and trails.</p> <hr/>

FIELD ASSISTANTS

[illegible]

CERTIFICATE OF SURVEY

We, James D. Claflin, Cadastral Surveyor, and Ryan R. Lorenzen, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day of April, 1997, we have dependently resurveyed a portion of the Eighth Guide Meridian West, through Township 47 North, between Ranges 64 and 65 West, portions of the south and west boundaries, the north boundary, and a portion of the subdivisional lines, Township 47 North, Range 65 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

DEC 13 1999

(Date)

DEC 13 1999

(Date)

James D. Claflin
(Cadastral Surveyor)

Ryan R. Lorenzen
(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of a portion of the Eighth Guide Meridian West, through Township 47 North, between Ranges 64 and 65 West, portions of the south and west boundaries, the north boundary, and a portion of the subdivisional lines, Township 47 North, Range 65 West, of the Sixth Principal Meridian, in the State of Wyoming, executed by Ryan R. Lorenzen, Surveying Technician, under the supervision of James D. Claflin, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

DEC 13 1999

(Date)

John P. Lee
(Signature of Authorized Officer)